# **SIGN SUPPLIER**




#### Stryder V2 Troughlight - New Features

#### Some of the new and updated features of the Stryder V2 Troughlight are:

- The system is now IP66 certified. The Connectors, Cable Glands & Blanking Plugs are IP68 rated.
- The system has a slimmer profile body.
- There are now joining connectors allowing the maximum system size to be limitless (single piece limited to 6m)
- The new lens design maximises illumination effect and optimises the light direction.









#### Stryder V2 Troughlight - Component Breakdown

## **IP68** Joining Connector

Connect Multiple troughlights together without any visible connections or cables.





MW121





White RAL9016





MW121 Silver is nearest match to silver Anodised main body





#### Slimmer Profile

Over 30% smaller than the previous troughlight design, with a closed profile to isolate power supply and cables.





#### **IP66** Certified

Full protection against dust and other similar particles.

Protection against powerful jets of water at a rate of 100 litre per minute (100kPa of Pressure)

3 year parts warranty



#### Stryder V2 Troughlight - Component Breakdown Continued...

#### **Optical Lens**

The new clear polycarbonate lens is designed to get the most from the 24v LED strips installed (cool White or warm White) in the troughlight giving even more illumination distance and optimising light direction.

The lens is sealed using a Neophene sponge cord to to stop dust/water ingress.





## **Main Body Extrusion**

The main troughlight extrusion comes at a maximum length of 6m. If a longer length is needed, multiple troughlights can be connected together using the IP68 joining connectors with no visible connections or cable.







The Stryder V2 6m trough light stock finishes are; Mill, Silver Anodised, White, Black & Bespoke RAL/BS colour **Powder Coating** 









# **End Cap Options**

Our Cast End Caps (left & Right) come in different paint options. The M16 Tapped hole is to mount either a cable gland or a blanking plug depending on which side you require the power cable exiting. Complete with a EPDM Sponge Rubber Gasket to seal the product.





MW121

Silver









**RAL9005** 





MW121 Silver is nearest match to silver Anodised main body







# M16 Cable Gland & **Blanking Plug Colours**









#### Stryder V2 Troughlight - Component Breakdown Continued...

# **Mounting Options**











Wall Bracket

Tray Bracket

**Double Bracket** 

**Channel Bracket** 

Panel Bracket

### **LED Colour Options**

Two LED colour temperature options available from stock.



24v warm White LED strip 3000k (1260lm/M)





24v cool White LED strip 6000k (1330lm/M)



# **Contact Us**

#### **Main Office**

Sign Supplier Unit 15 Dale Industrial Estate Radcliffe Manchester M26 1AD

#### **Contact**

0800 133 7555 info@signsupplier.co.uk



